

easypix® VX6330

6,36 MEGAPIXEL

SPECIFICATIONS

Image Sensor	Internal External	1/2.5" 6,36 Megapixel CCD Sensor
Active Pixels		6 Megapixel
Storage Media	Internal External	Built-in 32MB Flash Memory
		SD / MMC Card (Up to 1GB)
Sensor Sensitivity	Internal External	Auto or Manual (ISO 50, 100, 200, 400)
Lens		3X Optical Zoom Lens; F/2.6 (Wide) ~ 4,8 (Tele)
Focus Range	Normal Macro	50cm ~ Infinity 6cm
Still Image	Image File Format	JPEG (EXIF), DCF, DPOF, Direct Print (DPS)
	Image Resolution	0.3M, 2M, 4M, 7M, 10M (Firmware Interpolation)
Movie Clips	Movie File Format	MPEG4 (AVI, ASF, MOV)
	Movie Resolution	640 x 480 Pixels, 30 fps.; 320 x 240 Pixels, 30 fps.
Zoom		Optical Zoom 3X; Digital Zoom 4X
TFT Monitor		3" LTPS High Resolution Monitor, 960x240 Pixels
Strobe	Effective Range	0.5m ~ 3m
	Flash Modes	Auto / Force / Off / Red Eye Reduction Auto / Sunny / Cloudy / Tungsten / Fluorescent
White Balance		±2,0 EV (In 0.25EV Steps)
EV Compensation		5 sec. / 10 sec. / 20 sec.
Self-Timer		USB 2.0
PC Interface		NTSC / PAL
TV Out Format		Mechanical and Electronic Shutter, 2 ~ 1/2000 sec.
Shutter		Auto Power Off: Can Be Selected from Off, 1, 5 and 10 minutes
Auto Power Off		One Rechargeable Li-ion Battery
Power Supply		94 (W) x 63 (H) x 28 (D)mm
Dimensions		<142g (Without Batteries)
Weight		

Keep it real.



easypix®

Keep it real.